

VISTA-20SEUL



The VISTA-20SEUL is a microprocessor based partitioned security system that supports up to 38 zones using basic hardwired, wired expansion, and/or wireless zones, plus three keypad activated zones. Ideally equipped for light commercial burglary, this UL Listed control/communicator is extremely cost effective and versatile. Flexibility is the key for the VISTA-20SEUL. With its enhanced capabilities, this eight-zone control/communicator provides installation flexibility along with features that customers want in a UL Listed package costing much more. A host of easy to install and operate devices that include traditional hardwired and wireless technology supports the VISTA-20SEUL. In addition, powerful output control through relays and X-10 power line carrier receivers can activate lighting, HVAC, appliances and overhead garage doors.

FEATURES

- ◆ Eight zones stander
- ◆ Expandable to 38 zones
- ◆ 30 user codes (15 per partition)
- ◆ Two partitions
- ◆ 48 event log capacity
- ◆ Three authority levels
- ◆ Hardwired and wireless technology
- ◆ Temporal code compliant
- ◆ Supervised digital dialer
- ◆ Supports major communication format
- ◆ UL Commercial Burglary Listed

AGENCY LISTINGS

- ◆ UL609 Grade A Local Mercantile Premises and Mercantile Safe and Vault
- ◆ UL611/1610 Grades B Central Station
- ◆ UL365 Grades A Police Station Connected

Fire:

- ◆ California State Fire Marshall - Residential
- ◆ UL985 - Residential Fire

*VISTA-20SEUL...
never compromising
features with cost,
this delivers
powerful features in
a package that is
tailored to meet the
challenges of small
scale commercial
pplications.*

VISTA-20SEUL

APPLICATIONS

The VISTA-20SEUL partitioned security system is well suited for a variety of applications as a small sized burglary alarm control/communicator. A diverse line of ADEMCO initiating and control devices supports this extremely powerful control. Some of the applications supported are medical and professional buildings, supermarkets, churches or synagogues, day care centers, retail stores, fast food chains, service centers and health clubs.

INSTALLATION

The VISTA-20SEUL burglary security system has been designed to mount both quickly and easily in an attack resistant cabinet. It meets all applicable requirements for UL commercial burglary installations.

SPECIFICATIONS

Electrical:

Primary power:

120VAC to ADEMCO No. 1321 Transformer or 4300 if X-10 is used secondary rated 16.5AC, 25VA

Quiescent panel current draw:

100mA

Backup battery:

12VDC, 4.0AH max
Lead acid battery {gel type}

Alarm power:

12VDC, 2.0A max

Aux. standby power:

12VDC, 600mA max

Total power:

2.8A from all sources
For UL installations, combined aux and alarm output cannot exceed 700mA

Standby time:

Four hours with 400mA standby load using 4.0AH battery

Fusing:

Battery input fuse rated 3.0A (Use No. 90-12).

Dialer:

Line seize:

Double Pole

Ringer equiv.:

0.7B

Formats:

ADEMCO Low Speed, ADEMCO 4F2 Express, ADEMCO Contact ID, Sescoa and Radionics **Mechanical:**

Cabinet dimensions:

18"H X 14.5"W X 4.3"D

Environmental: Storage temp:

-10°C to 70°C

Operating temp:

0°C to 50°C

Humidity:

85% RH

EMI:

Meets or exceeds the following requirements:

- FCC Part 15, Class B Device
- FCC Part 68
- IEC EMC Directive

COMPATIBLE DEVICES

The complete line of ADEMCO hardwired and compatible wireless devices support the VISTA-20SE for commercial burglary applications.

Ordering Information

Part No.	Description
VISTA-20SEUL	Light Commercial Burglary Alarm Control