

**With the Vista-10SE, you're limited only by your desires and imagination**

**W**ith six zones and QED compatible 5800 wireless zone expansion, the Vista-10SE is the industry's most economical and sophisticated control that can operate lights and appliances, while providing 24 hour security. When placed in an ADEMCO Vista-ULKT enclosure the Vista-10SE is listed for UL609, UL365 and UL 610/1611 commercial burglary applications. In addition, the control supports scheduling capabilities and allows defined operations to be automated by pressing a single keypad button.



*The Vista - 10SE offers a new level of flexibility with superior security features, end user simplicity and powerful control.*

**End users will appreciate the easy-to-use convenience and control features of the Vista-10SE:**

- ◆ Six hardwired zones standard
- ◆ Expands to 22 zones/points
- ◆ Seven user codes
- ◆ Two-way downloading
- ◆ Supports up to four relays
- ◆ False alarm prevention features
- ◆ Supports wireless remote control
- ◆ Supports Vista Interactive Phone Module (VIP)
- ◆ Paging capabilities
- ◆ Quick exit features

# VISTA-10SE

## Security System

### APPLICATIONS

The Vista-10SE security system is well suited for a variety of applications as small sized burglary alarm control/communicator. A diverse line fo ADEMCO alarm notification appliances as well as initiating devices supports this powerful control. Some applications supported are convenience stores, medical or professional office suite, residential fire and burglary protection.

### INSTALLATION

The Vista-10SE security system has been designed to mount both quickly and easily in a convenient cabinet. When installed in a Vista-ULK, it meets applicable requirements for UL commercial burglary installations.

### SPECIFICATIONS

#### Electrical:

- 500mA, Aux - 12 VDC
- 16.5 VAC/25 VA transformer
- Alarm output 12 VDC, 2.0 amps max
- For UL installation, combined Aux and alarm output cannot exceed 600 mA

#### Communication:

- Touch tone or pulse

#### Formats:

- ADEMCO low speed, ADEMCO 4+2 express ademco contact ID, SESCOA/Radionics

#### Mechanical:

- Cabinet Dimensions: 14.5"H X 12.5"W X 3"D

#### Environmental:

- Storage Temp: -10°C to 70°C
- Operating Temp: 0°C to 50°C
- Humidity: 85% RH

#### EMI:

- Meets or exceeds the following requirements:
  - FCC Part 15, Class B Device
  - FCC Part 68
  - IEC EMC Directive

### AGENCY LISTINGS

The Vista-10SE has been approved for use in commercial burglary and residential fire and burglary applications. It has been listed under the following agency approvals:

#### Burglary:

- UL 609 Grade A Local Merchantile Premises, local Merchantile Safe and Vault
- UL 365 Grade A Police Station Connected
- UL 611/1610 Grade B Central Station
- UL 1023 Residential Burglary

#### Fire:

- California State Fire Marshall
- UL 985 Residential Fire

### COMPATIBLE DEVICES

The complete line of ADEMCO hardwired and QED compatible wireless devices support the Vista-10SE for commercial and residential applications.

### ORDERING INFORMATION

<u>Part No.</u>	<u>Description</u>
Vista-10SE	Control Panel