

Vista-20P SIA Modifications

This document summarizes the modifications made to this control panel in order to meet ANSI/SIA CP-01-2000 Standard for False Alarm Reduction. SIA compliance affects Entry/Exit, Dialer Delay, Auto Stay Arm, Cancel Verify and Swinger Suppression programming fields. The new default values are shown below.

Field Number	Function	Change	Previous Vista-20P	New Vista-20P
*34	Exit Delay Time	Selections	00-99 seconds	00-96 sec, 97 = 120
		Default Value	70/70	[60/60]
*35	Entry Delay #1	Selections	00-99	00-96, 97=120, 98=180, 99=240
*36	Entry Delay #2	Selections	00-99	00-96, 97=120, 98=180, 99=240
		Default Value	60,60	[30,30] (30 secs + 30 sec Dialer Delay)
*50	Dialer Delay	Selections	15 seconds Enable/Disable	0 – 45 seconds (in 15 seconds increments)
		Default Value	1 = 15 seconds	[2] = 30 seconds
*84	Auto Stay Arm	Default Value	0=No	[3] = both partitions
*86	Cancel Verify	Default Value	0=No	[1] = Yes
*93	Swinger Suppression	Default Value	0=Unlimited	[1] = 1 report



165 Eileen Way, Syosset NY 11791
Copyright© 2002 Pittway Corporation